

# MATERIAL SAFETY DATA SHEET

Prepared to U.S. OSHA, CMA, ANSI and Canadian WHMIS Standards

## 1. PRODUCT IDENTIFICATION

### CHEMICAL NAME; CLASS: NON-FLAMMABLE GAS MIXTURE

Containing One or More of the Following Components in a Nitrogen Balance Gas:

Carbon Monoxide, 0.0005-1.0%; Hydrogen, 0-2.0%; Methane, 0-2.5%; Oxygen, 0-23.5%

SYNONYMS: Not Applicable

CHEMICAL FAMILY NAME: Not Applicable

FORMULA: Not Applicable

Document Number: 50009

**Note:** The Material Safety Data Sheet is for this gas mixture supplied in cylinders with 33 cubic feet (935 liters) or less gas capacity (DOT - 39 cylinders). This MSDS has been developed for various gas mixtures with the composition of components within the ranges listed in Section 2 (Composition and Information on Ingredients). Refer to the product label for information on the actual composition of the product.

<b>PRODUCT USE:</b>	Calibration of Monitoring and Research Equipment
<b>SUPPLIER/MANUFACTURER'S NAME:</b>	CALGAZ, LLC
<b>ADDRESS:</b>	821 Chesapeake Drive Cambridge, MD 21613
<b>EMERGENCY PHONE:</b>	CHEMTREC: 1-800-424-9300
<b>BUSINESS PHONE:</b>	1-410-228-6400
General MSDS Information	1-713-868-0440
Fax on Demand:	1-800-231-1366

## 2. COMPOSITION and INFORMATION ON INGREDIENTS

CHEMICAL NAME	CAS #	mole %	EXPOSURE LIMITS IN AIR					
			ACGIH-TLV		OSHA-PEL		NIOSH IDLH	OTHER
			TWA ppm	STEL ppm	PEL ppm	STEL ppm		
Carbon Monoxide	630-08-0	0.0005-1.0%	25	NE	50 35 (Vacated 1989 PEL)	200 [ceiling] (Vacated 1989 PEL)	1200	NIOSH RELs:TWA = 35 STEL = 200 ceiling DFG MAKs:TWA = 30 PEAK = 2•MAK, 15 min., average value, 1 hr interval DFG MAK Pregnancy Risk Classification: B
Hydrogen	1333-74-0	0-2.0%	There are no specific exposure limits for Hydrogen. Hydrogen is a simple asphyxiant (SA). Oxygen levels should be maintained above 19.5%.					
Methane	74-82-8	0-2.5%	There are no specific exposure limits for Methane. Methane is a simple asphyxiant (SA). Oxygen levels should be maintained above 19.5%.					
Oxygen	7782-44-7	0-23.5%	There are no specific exposure limits for Oxygen. Oxygen levels should be maintained above 19.5%.					
Nitrogen	7727-37-9	Balance	There are no specific exposure limits for Nitrogen. Nitrogen is a simple asphyxiant (SA). Oxygen levels should be maintained above 19.5%.					

NE = Not Established.

See Section 16 for Definitions of Terms Used.

NOTE (1): ALL WHMIS required information is included in appropriate sections based on the ANSI Z400.1-1998 format. This product has been classified in accordance with the hazard criteria of the CPR and the MSDS contains all the information required by the CPR.

## 3. HAZARD IDENTIFICATION

**EMERGENCY OVERVIEW:** This product is a colorless, odorless gas. Carbon Monoxide, a component of this gas mixture, is a chemical asphyxiant and can produce significant, adverse health effects at relatively low concentrations. Over-exposure to Carbon Monoxide can cause nausea, dizziness, headaches, and collapse. Additionally, releases of this product may produce oxygen-deficient atmospheres (especially in small confined spaces or other poorly-ventilated environments); individuals in such atmospheres may be asphyxiated.

**SYMPTOMS OF OVER-EXPOSURE BY ROUTE OF EXPOSURE:** The most significant route of over-exposure for this product is by inhalation.

**INHALATION:** Due to the small size of an individual cylinder of this product, no unusual health effects from over-exposure to the product are anticipated under routine circumstances of use. Inhalation over-exposures to atmospheres containing more than the Threshold Limit Value of Carbon Monoxide (25 ppm) can result in serious health consequences. Carbon Monoxide is classified as a chemical asphyxiant, producing a toxic action by combining with the hemoglobin of the blood and replacing the available oxygen. Through this replacement, the body is deprived of the required oxygen, and asphyxiation occurs.

Since the affinity of carbon monoxide for hemoglobin is about 200-300 times that of oxygen, only a small amount of Carbon Monoxide will cause a toxic reaction to occur. Carbon Monoxide exposures in excess of 50 ppm will produce symptoms of poisoning if breathed for a sufficiently long time. If this product is released in a small, poorly ventilated area (i.e. an enclosed or confined space), symptoms which may develop include the following:

### CONCENTRATION OF CARBON MONOXIDE

### OBSERVED EFFECT

All exposure levels:

Over-exposure to Carbon Monoxide can be indicated by the lips and fingernails turning bright red.

200 ppm:

Slight symptoms (headache, discomfort) after several hours of exposure.

400 ppm:

Headache and discomfort experienced within 2-3 hours of exposure.

1,000 -2000 ppm:

Within 30 minutes, slight palpitations of the heart occurs. Within 1.5 hours, there is a tendency to stagger.

2000-2500 ppm:

Within 2 hours, there is mental confusion, headaches, and nausea. Unconsciousness within 30 minutes.

> 2500 ppm:

Potential for collapse and death before warning symptoms are produced.

Additionally, releases of this product may produce oxygen-deficient atmospheres (especially in small confined spaces or other poorly-ventilated environments); individuals in such atmospheres may be asphyxiated.

### HAZARDOUS MATERIAL IDENTIFICATION SYSTEM

HEALTH HAZARD	(BLUE)	2
---------------	--------	---

FLAMMABILITY HAZARD	(RED)	0
---------------------	-------	---

PHYSICAL HAZARD	(YELLOW)	0
-----------------	----------	---

### PROTECTIVE EQUIPMENT

EYES	RESPIRATORY	HANDS	BODY
------	-------------	-------	------

See Section 8

For Routine Industrial Use and Handling Applications

### 3. HAZARD IDENTIFICATION (continued)

**HEALTH EFFECTS OR RISKS FROM EXPOSURE: An Explanation in Lay Terms.** Over-exposure to this gas mixture may cause the following health effects:

**ACUTE:** Due to the small size of the individual cylinder of this product, no unusual health effects from exposure to the product are anticipated under routine circumstances of use. However, Carbon Monoxide (a component of this gas mixture) is toxic to humans. Symptoms of Carbon Monoxide poisoning can develop gradually, or can arise suddenly, depending on the concentration and duration of exposure. Lips and fingernails will turn bright red, which is a significant sign of Carbon Monoxide over-exposure. Other symptoms of over-exposure can include respiratory difficulty, headaches, shortness of breath, wheezing, headache, blurred vision, memory loss, dizziness, indigestion, nausea, unconsciousness, and death.

**CHRONIC:** Chronic exposure to oxygen-deficient atmospheres (below 18% oxygen in air) may effect the heart and nervous system. Clinical studies indicate that there is a relationship between exposure to Carbon Monoxide in specific occupations (i.e. fire-fighters, foundry workers) and an increased incidence of cardiovascular problems. Carbon Monoxide is a reproductive toxin. Refer to Section 11 (Toxicological Information) of this MSDS for further information.

**TARGET ORGANS:** ACUTE: Respiratory system, blood system. CHRONIC: Heart, cardiovascular system, central nervous system, reproductive system.

### 4. FIRST-AID MEASURES

**RESCUERS SHOULD NOT ATTEMPT TO RETRIEVE VICTIMS OF OVER-EXPOSURE TO THIS PRODUCT WITHOUT ADEQUATE PERSONAL PROTECTIVE EQUIPMENT.** At a minimum, **Self-Contained Breathing Apparatus and Fire-Retardant Personal Protective equipment should be worn. Adequate fire protection must be provided during rescue situations.** Victim(s) must be taken for medical attention. Rescuers should be taken for medical attention, if necessary. Take copy of label and MSDS to physician or other health professional with victim(s).

No unusual health effects are anticipated after exposure to this product, due to the small cylinder size. If any adverse symptom develops after over-exposure to this product, remove victim(s) to fresh air, as quickly as possible. Only Trained personnel should administer supplemental oxygen and/or cardio-pulmonary resuscitation, if necessary. Only trained personnel should administer supplemental oxygen.

**MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE:** Pre-existing respiratory conditions may be aggravated by over-exposure to this product. The Carbon Monoxide component of this gas mixture can aggravate some diseases of the cardiovascular system, such as coronary artery disease and angina pectoris.

**RECOMMENDATIONS TO PHYSICIANS:** Treat symptoms and reduce over-exposure. Provide oxygen. Hyperbaric oxygen is the most efficient antidote to Carbon Monoxide poisoning, the optimum range being 2-2.5 atm. A special mask, or, preferably, a compression chamber to utilize oxygen at these pressures is required. Avoid administering stimulant drugs.

### 5. FIRE-FIGHTING MEASURES

**FLASH POINT:** Not applicable.

**AUTOIGNITION TEMPERATURE:** Not applicable.

**FLAMMABLE LIMITS (in air by volume, %):**

Lower (LEL): Not applicable.

Upper (UEL): Not applicable.

**FIRE EXTINGUISHING MATERIALS:** Non-flammable gas mixture. Use extinguishing media appropriate for surrounding fire.


**UNUSUAL FIRE AND EXPLOSION HAZARDS:** This gas mixture is not flammable; however, containers, when involved in fire, may rupture or burst in the heat of the fire.

**Explosion Sensitivity to Mechanical Impact:** Not Sensitive.

**Explosion Sensitivity to Static Discharge:** Not Sensitive.

**SPECIAL FIRE-FIGHTING PROCEDURES:** Structural firefighters must wear Self-Contained Breathing Apparatus and full protective equipment.

#### NFPA RATING



### 6. ACCIDENTAL RELEASE MEASURES

**LEAK RESPONSE:** Due to the small size and content of the cylinder, an accidental release of this product presents significantly less risk of an oxygen deficient environment and other safety hazards than a similar release from a larger cylinder. However, as with any chemical release, extreme caution must be used during emergency response procedures. In the event of a release in which the atmosphere is unknown, and in which other chemicals are potentially involved, evacuate immediate area. Such releases should be responded to by trained personnel using pre-planned procedures. Proper protective equipment should be used. In case of a leak, clear the affected area, protect people, and respond with trained personnel.

For emergency disposal, secure the cylinder and slowly discharge the gas to the atmosphere in a well-ventilated area or outdoors. Allow the gas mixture to dissipate. If necessary, monitor the surrounding area (and the original area of the release) for oxygen and Carbon Monoxide. Carbon Monoxide level must be below exposure level listed in Section 2 (Composition and Information on Ingredients) before non-emergency personnel are allowed to re-enter area.

If leaking incidentally from the cylinder or its valve, contact your supplier.

### 7. HANDLING and USE

**WORK PRACTICES AND HYGIENE PRACTICES:** Be aware of any signs of dizziness or fatigue; exposures to fatal concentrations of this product could occur without any significant warning symptoms, due to oxygen deficiency. Do not attempt to repair, adjust, or in any other way modify the cylinders containing Carbon Monoxide. If there is a malfunction or another type of operational problem, contact nearest distributor immediately.

**STORAGE AND HANDLING PRACTICES:** Cylinders should be firmly secured to prevent falling or being knocked-over. Cylinders must be protected from the environment, and preferably kept at room temperature (approximately 21°C, 70°F). Cylinders should be stored in dry, well-ventilated areas, away from sources of heat, ignition, and direct sunlight. Protect cylinders against physical damage. Full and empty cylinders should be segregated. Use a first-in, first-out inventory system to prevent full containers from being stored for long periods of time. These cylinders are not refillable. **WARNING! Do not refill DOT 39 cylinders. To do so may cause personal injury or property damage.**

**SPECIAL PRECAUTIONS FOR HANDLING GAS CYLINDERS: WARNING!** Compressed gases can present significant safety hazards. During cylinder use, use equipment designed for these specific cylinders. Ensure all lines and equipment are rated for proper service pressure.

**PROTECTIVE PRACTICES DURING MAINTENANCE OF CONTAMINATED EQUIPMENT:** Follow practices indicated in Section 6 (Accidental Release Measures). Make certain that application equipment is locked and tagged-out safely. Always use product in areas where adequate ventilation is provided.

### 8. EXPOSURE CONTROLS - PERSONAL PROTECTION

**VENTILATION AND ENGINEERING CONTROLS:** No special ventilation systems or engineering controls are needed under normal circumstances of use. As with all chemicals, use this product in well-ventilated areas. If this product is used in a poorly-ventilated area, install automatic monitoring equipment to detect the levels of Carbon Monoxide and oxygen.

**RESPIRATORY PROTECTION:** No special respiratory protection is required under normal circumstances of use. Use supplied air respiratory protection if Oxygen levels are below 19.5%, or unknown, during emergency response to a release of this product. If respiratory protection is needed, use only protection authorized in the U.S. Federal OSHA Standard (29 CFR 1910.134), applicable U.S. State regulations, or the Canadian CSA Standard Z94.4-93 and applicable standards of Canadian Provinces. Oxygen levels below 19.16.33% are considered IDLH by OSHA. In such atmospheres, use of a full-facepiece pressure/demand SCBA or a full facepiece, supplied air respirator with auxiliary self-contained air supply is required under OSHA's Respiratory Protection Standard (1910.134-1998). In the event that exposure limits may be exceeded for Carbon Monoxide, the following NIOSH respiratory protection equipment guidelines should be consulted.

## 8. EXPOSURE CONTROLS - PERSONAL PROTECTION (continued)

### **CARBON MONOXIDE**

#### **CONCENTRATION**

Up to 350 ppm:  
Up to 875 ppm:  
Up to 1200 ppm:

#### **RESPIRATORY PROTECTION**

Any Supplied-Air Respirator (SAR).

Any SAR operated in a continuous-flow mode.

Any Air-Purifying, Full-Facepiece respirator (gas mask) with a chin-style, front- or back-mounted canister providing protection against Carbon Monoxide, or any Self-Contained Breathing Apparatus(SCBA) with a full facepiece, or any SAR with a full facepiece.

Emergency or Planned Entry into Unknown Concentrations or IDLH Conditions: Any SCBA that has a full facepiece and is operated in a pressure-demand or other positive-pressure mode, or any SAR that has a full facepiece and is operated in a pressure-demand or other positive-pressure mode in combination with an auxiliary SCBA operated in pressure-demand or other positive-pressure mode.

Escape: Any Air-Purifying, Full-Facepiece respirator (gas mask) with a chin-style, front- or back-mounted canister providing protection against Carbon Monoxide, or any appropriate escape-type, SCBA.

**EYE PROTECTION:** Safety glasses. If necessary, refer to U.S. OSHA 29 CFR 1910.133 or appropriate Canadian Standards.

**HAND PROTECTION:** No special protection is needed under normal circumstances of use. If necessary, refer to U.S. OSHA 29 CFR 1910.138 or appropriate Standards of Canada.

**BODY PROTECTION:** No special protection is needed under normal circumstances of use. If a hazard of injury to the feet exists due to falling objects, rolling objects, where objects may pierce the soles of the feet or where employee's feet may be exposed to electrical hazards, use foot protection, as described in U.S. OSHA 29 CFR 1910.136.

## 9. PHYSICAL and CHEMICAL PROPERTIES

The following physical property values are for the main component, Nitrogen:

**GAS DENSITY @ 32°F (0°C) and 1 atm:** .072 lbs/ ft<sup>3</sup> (1.153 kg/m<sup>3</sup>)

**BOILING POINT:** -320.4°F (-195.8°C)

**FREEZING/MELTING POINT @ 10 psig** -210°C (-345.8°F)

**SPECIFIC GRAVITY (air = 1) @ 70°F (21.1°C):** 0.906

**SOLUBILITY IN WATER vol/vol @ 32°F (0°C) and 1 atm:** 0.023

**EVAPORATION RATE (nBuAc = 1):** Not applicable.

**ODOR THRESHOLD:** Not applicable. Odorless.

**VAPOR PRESSURE @ 70°F (21.1°C) psig:** Not applicable.

**COEFFICIENT WATER/OIL DISTRIBUTION:** Not applicable.

**pH:** Not applicable.

**MOLECULAR WEIGHT:** 28.01

**EXPANSION RATIO:** Not applicable.

**SPECIFIC VOLUME (ft<sup>3</sup>/lb):** 13.8

The following values are for the gas mixture:

**APPEARANCE, ODOR AND COLOR:** This product is a colorless, odorless gas mixture.

**HOW TO DETECT THIS SUBSTANCE (warning properties):** There are no unusual warning properties associated with a release of this product.

## 10. STABILITY and REACTIVITY

**STABILITY:** Stable at normal temperature and pressure.

**DECOMPOSITION PRODUCTS:** The thermal decomposition products of Methane include carbon oxides. The other components of this gas mixture do not decompose, per se, but can react with other compounds in the heat of a fire.

**MATERIALS WITH WHICH SUBSTANCE IS INCOMPATIBLE:** Titanium will burn in Nitrogen (the main component of this product). Lithium reacts slowly with Nitrogen at ambient temperatures. Components of this product (Hydrogen, Carbon Monoxide, Methane) are also incompatible with strong oxidizers (i.e. chlorine, bromine pentafluoride, oxygen, oxygen difluoride, and nitrogen trifluoride). Carbon Monoxide is mildly corrosive to nickel and iron (especially at high temperatures and pressures).

**HAZARDOUS POLYMERIZATION:** Will not occur.

**CONDITIONS TO AVOID:** Contact with incompatible materials. Cylinders exposed to high temperatures or direct flame can rupture or burst.

## 11. TOXICOLOGICAL INFORMATION

**TOXICITY DATA:** The following toxicology data are available for the components of this product:

### **CARBON MONOXIDE:**

LC<sub>50</sub> (Inhalation-Rat) 1807 ppm/4 hours  
LC<sub>50</sub> (Inhalation-Mouse) 2444 ppm/4 hours  
LC<sub>50</sub> (Inhalation-Guinea Pig) 5718 ppm/4 hours  
LC<sub>50</sub> (Inhalation-wild bird species) 1334 ppm  
LCLo (Inhalation-Human) 4 mg/m<sup>3</sup>/12 hours:  
Behavioral: coma; Vascular: BP lowering not characterized in autonomic section; Blood: methemoglobinemia-carboxyhemoglobin  
LCLo (Inhalation-Man) 4000 ppm/30 minutes  
LCLo (Inhalation-Human) 5000 ppm/5 minutes  
LCLo (Inhalation-Dog) 4000 ppm/46 minutes  
LCLo (Inhalation-Rabbit) 4000 ppm  
LCLo (Inhalation-Mammal-species unspecified)

5000 ppm/5 minutes  
TCLo (Inhalation-Human) 600 mg/m<sup>3</sup>/10 minutes: Behavioral: headache  
TCLo (Inhalation-Man) 650 ppm/45 minutes:  
Blood: methemoglobinemia-carboxyhemoglobin; Behavioral: changes in psychophysiological tests  
TCLo (Inhalation-Rat) 1800 ppm/1 hour/14 days-intermittent: Cardiac: other changes  
TCLo (Inhalation-Rat) 30 mg/m<sup>3</sup>/8 hours/10 weeks-intermittent: Brain and Coverings: other degenerative changes;  
Behavioral: muscle contraction or spasticity  
TCLo (Inhalation-Rat) 96 ppm/24 hours/90 days-continuous: Blood: pigmented or

nucleated red blood cells, other changes  
TCLo (Inhalation-Rat) 250 ppm/5 hours/20 days-intermittent: Blood :pigmented or nucleated red blood cells, changes in other cell count (unspecified), changes in erythrocyte (RBC) count  
TDLo (Subcutaneous-Rat) 5983 mg/kg/18 weeks-intermittent: Blood: changes in serum composition (e.g. TP, bilirubin, cholesterol)  
TCLo (Inhalation-Mouse) 50 ppm/30 days-intermittent: Lungs, Thorax, or Respiration: structural or functional change in trachea or bronchi

TCLo (Inhalation-Monkey) 200 ppm/24 hours/90 days-continuous: Blood: pigmented or nucleated red blood cells, other changes  
TCLo (Inhalation-Rabbit) 200 mg/m<sup>3</sup>/3 hours/13 weeks-intermittent: Brain and Coverings: other degenerative changes; Cardiac: other changes; Blood: hemorrhage  
TCLo (Inhalation-Rabbit) 50 ppm/24 hours/8 weeks-continuous: Blood: changes in platelet count  
TCLo (Inhalation-Guinea Pig) 200 mg/m<sup>3</sup>/5 hours/4 weeks-intermittent: Endocrine: hyperglycemia  
TCLo (Inhalation-Guinea Pig) 200 mg/m<sup>3</sup>/5 hours/30 weeks-continuous: Cardiac: arrhythmias (including changes in conduction),  
EKG changes not diagnostic of specified effects, pulse rate increase, without fall in BP  
TCLo (Inhalation-Guinea Pig) 200 ppm/24 hours/90 days-continuous: Blood: pigmented or nucleated red blood cells, other changes  
TCLo (Inhalation-Rat) 75 ppm/24 hours: female 0-20 day(s) after conception: Reproductive: Maternal Effects: other effects; Effects on Newborn: behavioral  
TCLo (Inhalation-Rat) 150 ppm/24 hours: female 1-22 day(s) after conception: Reproductive: Specific Developmental

Abnormalities: cardiovascular (circulatory) system  
TCLo (Inhalation-Rat) 150 ppm/24 hours: female 1-22 day(s) after conception: Reproductive: Effects on Newborn: growth statistics (e.g.%, reduced weight gain), behavioral  
TCLo (Inhalation-Rat) 1 mg/m<sup>3</sup>/24 hours: female 72 day(s) pre-mating: Reproductive: Maternal Effects: menstrual cycle changes or disorders, parturition; Fertility: female fertility index (e.g. # females pregnant per # sperm positive females; # females pregnant per # females mated)  
TCLo (Inhalation-Rat) 150 ppm/24 hours: female 0-20 day(s) after conception: Reproductive: Effects on Newborn: behavioral  
TCLo (Inhalation-Rat) 75 ppm/24 hours: female 0-20 day(s) after conception: Reproductive: Specific Developmental Abnormalities: immune and reticuloendothelial system  
TCLo (Inhalation-Mouse) 65 ppm/24 hours: female 7-18 day(s) after conception: Reproductive: Effects on Newborn: behavioral  
TCLo (Inhalation-Mouse) 250 ppm/7 hours: female 6-15 day(s) after conception: Reproductive: Fertility: post-implantation

mortality (e.g. dead and/or resorbed implants per total number of implants); Specific Developmental Abnormalities: musculoskeletal system  
TCLo (Inhalation-Mouse) 125 ppm/24 hours: female 7-18 day(s) after conception: Reproductive: Effects on Embryo or Fetus: fetotoxicity (except death, e.g., stunted fetus)  
TCLo (Inhalation-Mouse) 8 pph/1 hour: female 8 day(s) after conception: Reproductive: Fertility: litter size (e.g. # fetuses per litter; measured before birth); Effects on Embryo or Fetus: fetotoxicity (except death, e.g., stunted fetus), fetal death  
TCLo (Inhalation-Mouse) 8 pph/1 hour: female 8 day(s) after conception: Reproductive: Specific Developmental Abnormalities: Central Nervous System  
TCLo (Inhalation-Rabbit) 180 ppm/24 hours: female 1-30 day(s) after conception: Reproductive: Effects on Newborn: stillbirth, viability index (e.g., # alive at day 4 per # born alive)  
Micronucleus Test (Inhalation-Mouse)1500 ppm/10 minutes  
Sister Chromatid Exchange (Inhalation-Mouse) 2500 ppm/10 minutes

### **HYDROGEN:**

There are no specific toxicology data for Hydrogen. Hydrogen is a simple asphyxiant (SA), which acts to displace oxygen in the environment.

### **METHANE:**

There are no specific toxicology data for Methane. Methane is a simple asphyxiant, which acts to displace oxygen in the environment.

### **NITROGEN:**

There are no specific toxicology data for Nitrogen. Nitrogen is a simple asphyxiant, which acts to displace oxygen in the environment.

## 11. TOXICOLOGICAL INFORMATION (continued)

### OXYGEN:

The toxicity data for Oxygen are related to exposures in a hyperbaric environment and are not likely to occur in industrial exposure situations.

**SUSPECTED CANCER AGENT:** The components of this gas mixture are not found on the following lists: FEDERAL OSHA Z LIST, NTP, CAL/OSHA, and IARC; therefore are not considered to be, nor suspected to be, cancer-causing agents by these agencies.

**IRRITANCY OF PRODUCT:** Contact with rapidly expanding gases can be irritating to exposed skin and eyes.

**SENSITIZATION OF PRODUCT:** The components of this gas mixture are not sensitizers.

**REPRODUCTIVE TOXICITY INFORMATION:** Listed below is information concerning the effects of this gas mixture on the human reproductive system.

**Mutagenicity:** The components of this gas mixture are not reported to cause mutagenic effects in humans.

**Embryotoxicity:** The components of this gas mixture are not reported to cause embryotoxic effects in humans.

**Teratogenicity:** This gas mixture is not expected to cause teratogenic effects in humans due to the small cylinder size and small total amount of all components. The Carbon Monoxide component of this gas mixture, which exists up to 1%, can cause teratogenic effects in humans. Severe exposure to Carbon Monoxide during pregnancy has caused adverse effects and the death of the fetus. In general, maternal symptoms are an indicator of the potential risk to the fetus since Carbon Monoxide is toxic to the mother before it is toxic to the fetus.

**Reproductive Toxicity:** The components of this gas mixture are not reported cause adverse reproductive effects in humans.

A *mutagen* is a chemical which causes permanent changes to genetic material (DNA) such that the changes will propagate through generation lines. An *embryotoxin* is a chemical which causes damage to a developing embryo (i.e. within the first eight weeks of pregnancy in humans), but the damage does not propagate across generational lines. A *teratogen* is a chemical which causes damage to a developing fetus, but the damage does not propagate across generational lines. A *reproductive toxin* is any substance which interferes in any way with the reproductive process.

**BIOLOGICAL EXPOSURE INDICES (BEIs):** Biological Exposure Indices (BEIs) have been determined for the Carbon Monoxide component, as follows:

CHEMICAL DETERMINANT	SAMPLING TIME	BEI
CARBON MONOXIDE • Carboxyhemoglobin in blood • Carbon monoxide in end-exhaled air	• End of shift • End of shift	• 3.5% of hemoglobin • 20 ppm

## 12. ECOLOGICAL INFORMATION

**ENVIRONMENTAL STABILITY:** The components of this gas mixture occur naturally in the atmosphere. The gas will be dissipated rapidly in well-ventilated areas.

**EFFECT OF MATERIAL ON PLANTS or ANIMALS:** No evidence is currently available on the effects of this gas mixture on plant and animal life. The Carbon Monoxide component of this gas mixture can be deadly to exposed animal life, producing symptoms similar to those experienced by humans. Carbon Monoxide may also be harmful to plant life.

**EFFECT OF CHEMICAL ON AQUATIC LIFE:** No evidence is currently available on this product's effects on aquatic life. The presence of more than a trace of the Carbon Monoxide component of this product is a hazard to fish.

## 13. DISPOSAL CONSIDERATIONS

**PREPARING WASTES FOR DISPOSAL PREPARING WASTES FOR DISPOSAL:** Waste disposal must be in accordance with appropriate U.S. Federal, State, and local regulations and those of Canada and its Provinces. Cylinders with undesired residual product may be safely vented outdoors with the proper regulator. For further information, refer to Section 16 (Other Information)

## 14. TRANSPORTATION INFORMATION

**THIS GAS MIXTURE IS HAZARDOUS AS DEFINED BY 49 CFR 172.101 BY THE U.S. DEPARTMENT OF TRANSPORTATION.**

**PROPER SHIPPING NAME:** Compressed gases, n.o.s. (\*Oxygen, Nitrogen)\*or the gas component with the next highest concentration next to Nitrogen.

**HAZARD CLASS NUMBER and DESCRIPTION:** 2.2 (Non-Flammable Gas)

**UN IDENTIFICATION NUMBER:** UN 1956

**PACKING GROUP:** Not applicable.

**DOT LABEL(S) REQUIRED:** Class 2.2 (Non-Flammable Gas)

**NORTH AMERICAN EMERGENCY RESPONSE GUIDEBOOK NUMBER (2000):** 126

**MARINE POLLUTANT:** The components of this gas mixture are not classified by the DOT as Marine Pollutants (as defined by 49 CFR 172.101, Appendix B)

**SPECIAL SHIPPING INFORMATION:** Cylinders should be transported in a secure position, in a well-ventilated vehicle. The transportation of compressed gas cylinders in automobiles or in closed-body vehicles can present serious safety hazards. If transporting these cylinders in vehicles, ensure these cylinders are not exposed to extremely high temperatures (as may occur in an enclosed vehicle on a hot day). Additionally, the vehicle should be well-ventilated during transportation.

**Note:** DOT 39 Cylinders ship in a strong outer carton (overpack). Pertinent shipping information goes on the outside of the overpack. DOT 39 Cylinders do not have transportation information on the cylinder itself.

**TRANSPORT CANADA TRANSPORTATION OF DANGEROUS GOODS REGULATIONS:** This gas mixture is considered as Dangerous Goods, per regulations of Transport Canada.

**PROPER SHIPPING NAME:** Compressed gases, n.o.s. (\*Oxygen, Nitrogen)\*or the gas component with the next highest concentration next to Nitrogen.

**HAZARD CLASS NUMBER and DESCRIPTION:** 2.2 (Non-Flammable Gas)

**UN IDENTIFICATION NUMBER:** UN 1956

**PACKING GROUP:** Not Applicable

**HAZARD LABEL:** Class 2.2 (Non-Flammable Gas)

**SPECIAL PROVISIONS:** None

**EXPLOSIVE LIMIT AND LIMITED QUANTITY INDEX:** 0.12

**ERAP INDEX:** None

**PASSENGER CARRYING SHIP INDEX:** None

**PASSENGER CARRYING ROAD VEHICLE OR PASSENGER CARRYING RAILWAY VEHICLE INDEX:** 75

**NORTH AMERICAN EMERGENCY RESPONSE GUIDEBOOK NUMBER (2000):** 126

**NOTE:** Shipment of compressed gas cylinders via Public Passenger Road Vehicle is a violation of Canadian law (Transport Canada Transportation of Dangerous Goods Act, 1992)

## 15. REGULATORY INFORMATION

### ADDITIONAL U.S. REGULATIONS:

**U.S. SARA REPORTING REQUIREMENTS:** The components of this gas mixture are not subject to the reporting requirements of Sections 302, 304 and 313 of Title III of the Superfund Amendments and Reauthorization Act., as follows:

**U.S. SARA THRESHOLD PLANNING QUANTITY:** There are no specific Threshold Planning Quantities for the components of this gas mixture. The default Federal MSDS submission and inventory requirement filing threshold of 10,000 lb (4,540 kg) may apply, per 40 CFR 370.20.

## 15. REGULATORY INFORMATION (Continued)

**U.S. TSCA INVENTORY STATUS:** The components of this gas mixture are listed on the TSCA Inventory.

**U.S. CERCLA REPORTABLE QUANTITIES (RQ):** Not applicable.

**U.S. STATE REGULATORY INFORMATION:** The components of this gas mixture are covered under the following specific State regulations:

**Alaska - Designated Toxic and Hazardous Substances:** Carbon Monoxide, Methane, Hydrogen.

**California - Permissible Exposure Limits for Chemical Contaminants:** Carbon Monoxide, Nitrogen, Methane, Hydrogen.

**Florida - Substance List:** Oxygen, Carbon Monoxide, Hydrogen.

**Illinois - Toxic Substance List:** Carbon Monoxide, Hydrogen.

**Kansas - Section 302/313 List:** No.

**Massachusetts - Substance List:** Oxygen, Carbon Monoxide, Methane, Hydrogen.

**Michigan - Critical Materials Register:** No.

**Minnesota - List of Hazardous Substances:** Carbon Monoxide, Methane, Hydrogen.

**Missouri - Employer Information/Toxic Substance List:** Methane, Hydrogen

**New Jersey - Right to Know Hazardous Substance List:** Oxygen, Carbon Monoxide, Nitrogen, Methane, Hydrogen.

**North Dakota - List of Hazardous Chemicals, Reportable Quantities:** No.

**Pennsylvania - Hazardous Substance List:** Oxygen, Carbon Monoxide, Nitrogen, Methane, Hydrogen.

**Rhode Island - Hazardous Substance List:** Oxygen, Carbon Monoxide, Nitrogen, Methane, Hydrogen.

**Texas - Hazardous Substance List:** No.

**West Virginia - Hazardous Substance List:** No.

**Wisconsin - Toxic and Hazardous Substances:** No.

**CALIFORNIA SAFE DRINKING WATER AND TOXIC ENFORCEMENT ACT (PROPOSITION 65):** Carbon Monoxide is on the California Proposition 65 lists. **WARNING:** This gas mixture contains a chemical known to the State of California to cause birth defects or other reproductive harm.

### OTHER U.S. FEDERAL REGULATIONS:

- Carbon Monoxide is subject to the reporting requirements of CFR 29 1910.1000. Carbon Monoxide is listed on Table Z.1.
- Hydrogen and Methane are subject to the reporting requirements of Section 112(r) of the Clean Air Act. The Threshold Quantity for each of these gases is 10,000 pounds and so this mixture will not be affected by the regulation.
- This gas mixture does not contain any Class I or Class II ozone depleting chemicals (40 CFR part 82).
- Nitrogen and Oxygen are not listed as Regulated Substances, per 40 CFR, Part 68, of the Risk Management for Chemical Releases. Carbon Monoxide, Methane, and Hydrogen are listed under this regulation in Table 3 as Regulated Substances (Flammable Substances), in quantities of 10,000 lbs (4,553 kg) or greater, and so this mixture will not be affected by the regulation.

### ADDITIONAL CANADIAN REGULATIONS:

**CANADIAN DSL/NDL INVENTORY STATUS:** The components of this gas mixture are on the DSL Inventory.

**CANADIAN ENVIRONMENTAL PROTECTION ACT (CEPA) PRIORITIES SUBSTANCES LISTS:** The components of this gas mixture are not on the CEPA Priorities Substances Lists.

**OTHER CANADIAN REGULATIONS:** This gas mixture is categorized as a Controlled Product, Hazard Classes A and D2A, as per the Controlled Product Regulations.

## 16. OTHER INFORMATION

### INFORMATION ABOUT DOT-39 NRC (Non-Refillable Cylinder) PRODUCTS

DOT 39 cylinders ship as hazardous materials when full. Once the cylinders are relieved of pressure (empty) they are not considered hazardous material or waste. Residual gas in this type of cylinder is not an issue because toxic gas mixtures are prohibited. Calibration gas mixtures typically packaged in these cylinders are Nonflammable n.o.s., UN 1956. A small percentage of calibration gases packaged in DOT 39 cylinders are flammable or oxidizing gas mixtures.

For disposal of used DOT-39 cylinders, it is acceptable to place them in a landfill if local laws permit. Their disposal is no different than that employed with other DOT containers such as spray paint cans, household aerosols, or disposable cylinders of propane (for camping, torch etc.). When feasible, we recommended recycling for scrap metal content. CALGAZ, LLC will do this for any customer that wishes to return cylinders to us prepaid. All that is required is a phone call to make arrangements so we may anticipate arrival. Scrapping cylinders involves some preparation before the metal dealer may accept them. We perform this operation as a service to valued customers who want to participate.

**MIXTURES:** When two or more gases or liquefied gases are mixed, their hazardous properties may combine to create additional, unexpected hazards. Obtain and evaluate the safety information for each component before you produce the mixture. Consult an Industrial Hygienist or other trained person when you make your safety evaluation of the end product. Remember, gases and liquids have properties which can cause serious injury or death.

Further information about the handling of compressed gases can be found in the following pamphlets published by: Compressed Gas Association Inc. (CGA), 1725 Jefferson Davis Highway, Suite 1004, Arlington, VA 22202-4102. Telephone: (703) 412-0900.

- P-1 "Safe Handling of Compressed Gases in Containers"  
AV-1 "Safe Handling and Storage of Compressed Gases"  
"Handbook of Compressed Gases"

### PREPARED BY:

CHEMICAL SAFETY ASSOCIATES, Inc.  
PO Box 3519, La Mesa, CA 91944-3519  
619/670-0609

Fax on Demand: 1-800/231-1366



This Material Safety Data Sheet is offered pursuant to OSHA's Hazard Communication Standard, 29 CFR, 1910.1200. Other government regulations must be reviewed for applicability to this product. To the best of CALGAZ, LLC knowledge, the information contained herein is reliable and accurate as of this date; however, accuracy, suitability or completeness are not guaranteed and no warranties of any type, either express or implied, are provided. The information contained herein relates only to this specific product. If this product is combined with other materials, all component properties must be considered. Data may be changed from time to time. Be sure to consult the latest edition.